EXHIBIT G

Claim 15	**eTech Parts Plus 822-9401 OLED Display (“ETP-822-9401”)**
15[pre] A pixel circuit in an organic light emitting device, comprising:	The ETP-822-9401 includes an organic light-emitting diode (“OLED”) display. 

Claim 15	**eTech Parts Plus 822-9401 OLED Display ("ETP-822-9401")**
15[pre] A pixel circuit in an organic light emitting device, comprising: (*cont'd*)	The ETP-822-9401 comprises a pixel circuit in an organic light-emitting device. The annotated backside image (*below left*) shows a pixel circuit of the eTech Parts 822-9401, including transistors (**T1**–**T7**) and a capacitor (**Cst**). An exemplary circuit diagram of the pixel circuit of the eTech Parts 822-9401 is also shown (*below right*).  

Claim 15	**eTech Parts Plus 822-9401 OLED Display ("ETP-822-9401")**
15[a] a first transistor including a gate to which a current scan signal is applied, and a source to which a data signal voltage is applied;	The pixel circuit of the ETP-822-9401 has a first transistor including a gate to which a current scan signal is applied, and a source to which a data signal voltage is applied. As shown in the annotated backside image below, a source of the first transistor **T2** is coupled to a data line **DATA[m]** for delivering a data signal voltage. The gate of first transistor **T2** is coupled to a scan line **SCAN[n]** that provides a current scan line signal. In response to an active (low) current scan line signal delivered on scan line **SCAN[n]**, first transistor **T2** delivers a data signal voltage from data line **DATA[m]**.  

Claim 15	**eTech Parts Plus 822-9401 OLED Display ("ETP-822-9401")**
15[a] a first transistor including a gate to which a current scan signal is applied, and a source to which a data signal voltage is applied; *(cont'd)*	For example, as shown in the exemplary annotated images below, in response to an active (low) current scan line signal (blue line) delivered on scan line **SCAN[n]**, first transistor **T2** delivers the data signal voltage (red line) present on data line **DATA[m]**. The annotated images below depict an exemplary voltage path from data line **DATA[m]** through transistors **T2-T1-T3** to the gate of transistor **T1**. **Delivery of Data Signal Voltage (backside image)**  **Delivery of Data Signal Voltage (front-side image)** 

Claim 15	**eTech Parts Plus 822-9401 OLED Display ("ETP-822-9401")**
15[b] a second transistor whose source is coupled to a drain of the first transistor;	The pixel circuit of the ETP-822-9401 has a second transistor whose source is coupled to a drain of the first transistor. As shown in the annotated backside image below, the source of the second transistor **T1** is coupled to the drain of first transistor **T2**.  

Claim 15	**eTech Parts Plus 822-9401 OLED Display ("ETP-822-9401")**
15[c] a third transistor whose drain and source are connected between a gate and a drain of the second transistor;	The pixel circuit of the ETP-822-9401 has a third transistor whose drain and source are connected between a gate and a drain of the second transistor. As shown in the annotated backside image below, a third transistor **T3** has drain and source electrodes connected between gate and drain electrodes of the second transistor **T1**, respectively.  

Claim 15	**eTech Parts Plus 822-9401 OLED Display ("ETP-822-9401")**
15[d] a fourth transistor including a gate to which a current light-emitting signal is applied, a source to which a power supply voltage is applied, and a drain coupled to the source of the second transistor;	The pixel circuit of the ETP-822-9401 has a fourth transistor including a gate to which a current light-emitting signal is applied, a source to which a power supply voltage is applied, and a drain coupled to the source of the second transistor. In the annotated backside image below, a fourth transistor **T5** has a source coupled to **ELVDD** and a drain coupled to the source of transistor **T1**. In response to an active (low) current light-emitting signal delivered on emission line **EM[n]**, fourth transistor **T5** delivers a power supply voltage from **ELVDD** to second transistor **T1**.  

Claim 15	**eTech Parts Plus 822-9401 OLED Display ("ETP-822-9401")**
15[e] a fifth transistor including a gate to which the current light-emitting signal is applied, a source coupled to the drain of the second transistor, and a drain coupled to one terminal of an electroluminescent element;	The pixel circuit of the ETP-822-9401 has a fifth transistor including a gate to which the current light-emitting signal is applied, a source coupled to the drain of the second transistor, and a drain coupled to one terminal of an electroluminescent element. In the annotated backside image below, a fifth transistor **T6** has a source coupled to a drain of second transistor **T1**, and a drain is coupled to one terminal of an electroluminescent element (**OLED**) through a contact hole. As further shown in the annotated image below, in response to an active (low) current light-emitting signal delivered on emission line **EM[n]**, fifth transistor **T6** turns on and delivers driving current that flows through second transistor **T1** to the **OLED**.  

Claim 15	**eTech Parts Plus 822-9401 OLED Display ("ETP-822-9401")**
15[f] the electroluminescent element having the one terminal coupled to the drain of the fifth transistor and the other terminal grounded; and	The pixel circuit of the ETP-822-9401 has an electroluminescent element with one terminal coupled to the drain of the fifth transistor and the other terminal grounded. As shown in the annotated backside image below, the pixel circuit has an electroluminescent element (**OLED**) with a first terminal, the anode, coupled to the drain of the fifth transistor **T6**. The other terminal of the **OLED** is grounded to facilitate the flow of current from fifth transistor **T6** through the anode of the **OLED** to the cathode in the light-emission phase.  

Claim 15	**eTech Parts Plus 822-9401 OLED Display ("ETP-822-9401")**
15[g] a capacitor in which one terminal of the capacitor is coupled to the gate of the second transistor and a power supply voltage is applied to the other terminal of the capacitor.	The pixel circuit of the ETP-822-9401 has a capacitor in which one terminal of the capacitor is coupled to the gate of the second transistor and a power supply voltage is applied to the other terminal of the capacitor. As shown in the annotated backside image below, blue dashes outline the lower plate of the capacitor **Cst**, which is coupled to the gate of the second transistor **T1**.  

Claim 15	**eTech Parts Plus 822-9401 OLED Display ("ETP-822-9401")**
15[g] a capacitor in which one terminal of the capacitor is coupled to the gate of the second transistor and a power supply voltage is applied to the other terminal of the capacitor. (*cont'd*)	As shown in the annotated front-side image below, red dashes outline the upper plate of the capacitor **Cst** that is coupled to the power supply voltage **ELVDD**.